



# CERTIFICATE OF CONFORMITY

This is to certify that



## HomeGuard Precision Termite Management System

### Product description

**HomeGuard TMB**, 0.2mm sheet with Bifenthrin incorporated, for underslab installations and joints.

**HomeGuard DPC**, 0.5mm sheet with Bifenthrin incorporated, for perimeter (cavity) installations.

**HomeGuard Blue**, 0.25mm sheet with Bifenthrin incorporated for perimeter (cavity) installations.

**HomeGuard GT**, Granules with Bifenthrin incorporated in it, for perimeter (cavity) installations.

**HomeGuard Collars (40mm 50mm, 80mm, 100mm)**, Rigid plastic collars with Bifenthrin incorporated, for penetrations

### Product purpose or use

An underslab, perimeter and penetration system to deter concealed entry by subterranean termites into a building.

### Certificate holder

**FMC Australasia Pty Ltd**  
ABN 45 095 326 891  
26/8 Metroplex Avenue  
Murrarie QLD 4172

### Codemark certification body

SAI Global Certification Services Pty Limited  
(ACN 108 716 669) Trading as "SAI Global"  
JAS-ANZ Accreditation No. Z1440295AS  
Address: 286 Sussex Street, Sydney, NSW 2000  
Website: [www.saiglobal.com](http://www.saiglobal.com)

### Complies with the Building Code of Australia (BCA):

1. Volume One: BP1.1 and BP1.2 (*limited only to actions by subterranean termites*)
2. Volume Two: P2.1 (*limited only to actions by subterranean termites*)
3. State Additions: Volume Two: QLD P2.1.1 (*limited only to actions by subterranean termites*)

### Subject to the following conditions and limitations:

1. The FMC HomeGuard Precision Termite Management System is to be installed by licensed installers trained and approved by FMC Australasia Pty Ltd.
2. The FMC HomeGuard Precision Termite Management System is to be installed in accordance with FMC HomeGuard installation manual (Version 4 2010).
3. The 0.25mm, 0.5mm thick HomeGuard sheet and the HomeGuard GT when used across a perimeter cavity treatment must finish at least 75mm above the surrounding finished ground level.
4. In all cases a cover strip is to be laid on top of the HomeGuard GT barrier course of bricks so that the cover strip extends at least 20mm over the top of the granules and is within contact with the granules as specified in the Installation Manual.
5. Penetrations of a different size to the preformed HomeGuard collar are to be protected using the HomeGuard sheet collars made as described in the installation manual
6. The HomeGuard collars are not to be glued to any of the penetrations that they protect as described in the installation manual.
7. When used in conjunction with a concrete slab, the concrete slab must be designed and constructed in accordance with the requirements of AS 2870-1996 Residential slabs and footings (*as amended up to and including Amendment 4*) or AS 3600-2001 - Concrete Structures (*as amended up to and including Amendment 2*).
8. Inspections are undertaken annually in accordance with the FMC HomeGuard installation manual to determine that no bridging or breaching of the barrier has occurred.

Alex Ezrakovich

General manager Certification  
For and on behalf of SAI Global

Unrestricted  
Building Certifier

19/07/2010

Date of issue

18/07/2013

Date of expiry

CM20003

Certificate Number



- This Certificate of Conformity is issued under arrangement with JAS-ANZ. The ABCB does not in any way warrant or represent that the Product the subject of this Certificate of Conformity conforms with the BCA, nor accepts any liability arising out of the use of the Product.
- It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the ABCB website, [www.abcb.gov.au](http://www.abcb.gov.au).